1738

ENGINEER'S

LEVEL BOOK

No. 4 of 5

EUGENE DIETZGEN CO.

DRAWING MATERIALS, MATHEMATICAL and SURVEYING INSTRUMENTS

Chicago New York San Francisco New Orleans Pittsburg Toronto

Distances from Center of Roadway for Cross-Sectioning
Roadway 16 feet wide. Side Slopes 1 on 1.
For Single Track Embankment.

H	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	H
0	8.0	8.1	8.2	8.3	8.4	8.5	8.6	8.7	8.8	8.9	0
1	9.0	9.1	9.2	9.3	9.4	9.5	9.6	9.7	9.8	9.9	1
2	10.0	10.1	10.2	10.3	10.4	10.5	10.6	10.7	10.8	10.9	2
3	11.0	11.1	11.2	11.3	11.4	11.5	11.6	11.7	11.8	11.9	3
4	12.0	12.1	12.2	12.3	12.4	12.5	12.6	12.7	12.8	12.9	4
5	13.0	13.1	13.2	13.3	13.4	13.5	13.6	13.7	13.8	13.9	5
6	14.0	14.1	14.2	14.3	14.4	14.5	14.6	14.7	14.8	14.9	6
7	15.0	15.1	15.2	15.3	15.4	15.5	15.6	15.7	15.8	15.9	7
8	16.0	16.1	16.2	16.3	16.4	16.5	16.6	16.7	16.8	16.9	8
9	17.0	17.1	17.2	17.3	17.4	17.5	17.6	17.7	17.8	17.9	9
10	18.0	18.1	18.2	18.3	18.4	18.5	18.6	18.7	18.8	18.9	10
11	19.0	19.1	19.2	19.3	19.4	19.5	19.6	19.7	19.8	19.9	11
12	20.0	20.1	20.2	20.3	20.4	20.5	20.6	20.7	20.8	20.9	12
13	21.0	21.1	21.2	21.3	21.4	21.5	21.6	21.7	21.8	21.9	13
14	22.0	22.1	22.2	22.3	22.4	22.5	22.6	22.7	22.8	22.9	14
15	23.0	23.1	23.2	23.3	23.4	23.5	23.6	23.7	23.8	23.9	15
16	24.0	24.1	24.2	24.3	24.4	24.5	24.6	24.7	24.8	24.9	16
17	25.0	25.1	25.2	25.3	25.4	25.5	25.6	25.7	25.8	25.9	17
18	26.0	26.1	26.2	26.3	26.4	26.5	26.6	26.7	26.8	26.9	18
19	27.0	27.1	27.2	27.3	27.4	27.5	27.6	27.7	27.8	27.9	19
20	28.0	28.1	28.2	28.3	28.4	28.5	28.6	28.7	28.8	28.9	20
21	29.0	29.1	29.2	29.3	29.4	29.5	29.6	29.7	29.8	29.9	21
22	30.0	30.1	30.2	30.3	30.4	30.5	30.6	30.7	30.8	30.9	22
23	31.0	31.1	31.2	31.3	31.4	31.5	31.6	31.7	31.8	31.9	23
24	32.0	32.1	32.2	32.3	32.4	32.5	32.6	32.7	32.8	32.9	24
25	33.0	33.1	33.2	33.3	33.4	33.5	33.6	33.7	33.8	33.9	25
26	34.0	34.1	34.2	34.3	34.4	34.5	34.6	34.7	34.8	34.9	26
27	35.0	35.1	35.2	35.3	35.4	35.5	35.6	35.7	35.8	35.9	27
28	36.0	36.1	36.2	36.3	36.4	36.5	36.6	36.7	36.8	36.9	28
29	37.0	37.1	37.2	37.3	37.4	37.5	37.6	37.7	37.8	37.9	29
30	38.0	38.1	38.2	38.3	38.4	38.5	38.6	38.7	38.8	38.9	30
31	39.0	39.1	39.2	39.3	39.4	39.5	39.6	39.7	39.8	39.9	31
32	40.0	40.1	40.2	40.3	40.4	40.5	40.6	40.7	40.8	40.9	32
33	41.0	41.1	41.2	41.3	41.4	41.5	41.6	41.7	41.8	41.9	33
34	42.0	42.1	42.2	42.3	42.4	42.5	42.6	42.7	42.8	42.9	34
35	43.0	43.1	43.2	43.3	43.4	43.5	43.6	43.7	43.8	43.9	35
36	44.0	44.1	44.2	44.3	44.4	44.5	44.6	44.7	44.8	44.9	36
37	45.0	45.1	45.2	45.3	45.4	45.5	45.6	45.7	45.8	45.9	37
38	46.0	46.1	46.2	46.3	46.4	46.5	46.6	46.7	46.8	46.9	38
39	47.0	47.1	47.2	47.3	47.4	47.5	47.6	47.7	47.8	47.9	39
40	48.0	48.1	48.2	48.3	48.4	48.5	48.6	48.7	48.8	48.9	40

Example—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 30.6. For same slopes but other widths of roadbed, correct above figures by one-half difference in width of roadbed; thus in example above, for 20 ft. roadbed distance will be 30.6+(20—16)÷2 or 2 ft. added to 30.6 =32.6. For slopes of 1 on 1½ see inside of back cover.

Copyright, 1914, by Eugene Dietzgen Co.

F. B. 1738

This Field Book is manufactured of a High Grade 50% Rag Paper having a WATER RESISTING SURFACE, and is sewed with Bing Special Enamel Waterproof thread.

Made in U. S. A.

Traverse Line for Topography and Location of Prop. Road from 54th & F.L. Cajon to Montezuma Road.

(Levels P-12)

Begin on ext.? Hub - call 3+50 Turned 39° 15' 15" Lt. from long chord produced

9-27-46

Osborne Hendricks
Hardin Beck
Worrell Greer

Indexed E.S.K.

1



13+25.83 - Hub. Angle 06° 20' 15" Rt.
on point of Ridge. ℄ Creek = 61' Lt.

12+16 = ℄ side creek

11+16.70 = Hub on Sly. side of Draw -

8+66.70 = Nail on ℄ of small ridge

5+91.70 = Hub. on point of ridge



18+51.80 - Ang. 12° 04' 15" Rt. - 19' Lt. = ℄ Creek



Thru Heavy brush

24+69.30 = Angle 22° 32' 15" Rt.

Bottom of Valley - 35' Rt. = ℄ Creek







21+23.72 = Angle 3° 17' Rt.

Point of flat ridge - 34' Ht. = ℄ Creek

Brush

36+00 = nail

32+20 = ℄ Creek

32+03.90 = 290' slope - nail

29+14.54 - Hng. 6° 08' 45" lt. - top of narrow ridge - 42' Lt. = ℄ Creek

28+70 = Mouth of Deep draw

Brush

26+59.30 = Nail. Dist. only



42+10.77 = P.O.T. Nail

41+60 - 12' Lt. = int. of 2 creeks

38+94.36 = Ang. 33° 56' 30" Lt. = Hub in clear spot on Pt. of Ridge - 100' up from bottom



Deep canyon

47+19.61 = Hub on Point of ridge P.O.T.

45+27.26 = P.O.T. Nail on break in slope of Hill



10-3-46

51+45.50 = Hub on Top of cut on S. side of Montezuma Road Angle 110° 44' Rt.



64+67.61 to E.C.

Dist. Computed for Long Chord.

59+56.57 - Fd. spike in pave Ang. 14° 45' Rt. to RR spike on E.C.

59+53.01 - Fd. spike in pave - Ang. 2° 24' 15" Rt.

55+51.41 - Hub on S. shoulder Rd. Angle 19° 48' 45" Lt.



10-4-46

69+15.39 = P.I. Ang. 23° 20' Rt.

66+67.61 = B.C. Ang. 14°45'

64+67.61 = E.C. Ang. 14° 45' Rt.



76+44.19 - Nail in pave 75° 51' 45" Rt
Set on Dist. shown in 1498-50 + 5403-L



Levels on ℄ for Traverse points.

Location: Traverse P-1-11

B.M.	3.92	407.69		403.77	S.E. B.P. 54± + Elev
3+50 = ℄ Hub.			8.42	399.27	
	1.13	400.40	11.16	389.24	
	0.49	389.73			
5+91.70 = Hub.			9.50	380.23	
#3 T.P.	0.36	378.90	11.19	378.54	
#4 T.P.	0.17	366.90	12.17	366.73	
#5 T.P.			12.01	354.89	stake
					5+91.70
	0.83	381.06		380.23	
#6 T.P.	0.42	367.11	14.37	366.69	
#7 T.P.	0.26	357.00	10.37	356.74	on Top 8+56 3/4 Valve
			2.95	354.05	Ground 8+66.70
#8 T.P.	0.81	343.25	14.56	342.44	
#9 T.P.	3.78	336.95	10.08	333.17	on Hub 11+16.70
13+25.8 Hub			6.45	330.50	
#10 T.P.	2.24	325.38	13.81	323.14	on Rock
#11 T.P.	3.26	314.78	13.86	311.52	
#12 T.P.	2.00	310.94	5.84	308.94	on Hub 18+51.80

Cont. P-13

Levels Cont. from P-12

310.94

21+23.72 on Hub			8.93	302.01	
#13 T.P.	0.34	298.22	13.06	297.88	on Rock
#14 T.P.	2.84	290.12	10.87	287.35	on Hub 24+69.30
on Rim Sewer MH.			11.50	278.69	
#15 T.P.	2.69	279.94	12.94	277.25	
29+14.54 on Hub			1.04	278.90	
#16 T.P.	2.04	269.04	12.94	267.00	on Peg
#17 T.P.	2.24	258.85	12.43	256.61	on Peg.
#18 T.P.	13.00	259.23	12.62	246.23	" "
#19 T.P.	7.49	264.87	1.85	257.38	
38+94.36 on Hub			0.98	264.39	
#20 T.P.	0.45	252.26	13.06	251.81	
#21 T.P.	9.39	248.83	12.82	239.44	on Peg.
#22 T.P.	12.89	260.51	1.21	247.62	" Rock
#23 T.P.	8.81	268.79	0.53	259.98	
#24 T.P.	12.80	278.48	3.11	265.68	
#25 T.P.	4.49	282.12	0.85	277.63	on Peg.
47+19.61-P.O.T. Hub			2.97	279.15	Hub
#26 T.P.			9.36	272.76	on Hub 51+45.50

Check Levels - B.M.s
Pages 12 - 14

	3.11	406.88		403.77	B.M. S.F. B.P. 54th + El (Cyon
3+50	7 Hub		7.60	399.28	.01
T.P. #1-B	1.68	396.26	12.30	394.58	
T.P. #2-B	1.59	385.12	12.73	383.53	
5+91.70	= Hub.		4.89	380.23	✓
T.P. #3-B	0.63	372.89	12.86	372.26	
T.P. #4-B	1.86	361.79	12.96	359.93	
Chk Top	3/4 Hyd		5.02	356.77	0.03 High 8+50
T.P. 5-B	053	349.26	13.06	348.73	
T.P. #6-B	8.32	338.35	11.23	338.03	
11+16.7	Nail		5.17	333.18	.01 High
13+25	83 on Hub		7.83	330.52	.02 "
T.P. #7-B	1.94	326.78	13.01	325.34	on Peg.
T.P. 8-B	1.64	315.82	12.60	314.18	on "
T.P. 9-B	1.79	310.78	6.83	308.99	on Hub 18+51.80
Chk. 21+23.72		Hub	8.72	302.06	0.05 High
T.P. #10-B	0.94	298.70	13.02	297.76	
T.P. #11-B	2.77	290.17	11.30	287.40	on Hub. 24+69.30
Chk. Rim Sewer MH			11.43	278.74	
T.P. #12-B	2.67	280.46	12.38	277.79	

Cont. P. 15

Check Levels Cont. from P-14

	280.46			
chk 29+14.54 = Hub		1.52	278.94	
TP #13-B	1.85	269.95	12.36	268.10	
TP #14-B	11.48	271.06	10.37	259.58	on Rock
Chk Hub			6.65	264.41	on Hub 38+94.36
TP #15B	12.72	281.15	2.63	268.43	
47+19.61 = Hub			2.00	279.15 ✓	
51+45.50 = Hub			8.41	272.74	
				272.76 = P-13	
				0.02 Error.	
In Trail on Stick-Peg	in circle of Rocks		0.03	281.12	W. Side Canyon


Fd. 1/4" Iron Pipe
R.E. 4847
B.C. Rt.
115.52'
Fd. 1/4 Iron Pipe
& Disk R.E. 4847
312.40'
C.T.
Fd. C.T. Ld.
&
Fd. C.T. Ld.
Collier Ave.
20
30'
30'
320.15'
SYTH
Fd. C.T. Ld.
Adams Ave
43'
23'
30
1034.90'
Cont. on
Lower Lt Page
320.15'
Fd. C.T.
43'
Adams Ave.
Fd. Ld
& Tack
180°54'
1034.90'
90°
23'
30'
579.70'
def 4°56'30"
long chd on 7' Line = 348.85'
= Meas.
4°57'30"
20'
30'
3450
page 1
186
104.03'
Grid. Book 162
8°57'
SYTH
Street
15.63'
0+00
El Cajon
Blvd.

Walker T
Becker
Greer
11-2-46

Supplementary Stadia Topography

54th St. Extension

Readings from Station 47+19.6' Elev.=27.16 HI=5.0

Readings to Left from Forward Tan.

Station	Azimuth	Stadia	V Δ	Horiz. D.	Diff Elev	True Elev
	23°50'	670	-3°21'	668	-39.1	240.1
	26°15'	763	-2°36'	763	-35.3	243.9
	26°40'	696'	6.0 -4°20'	694	-54.4 ~~-53.8~~	224.8 ~~225.4~~
	30°43'	897'	-2°39'	897	-44.9	234.3
Conc. Culvert	27°31'	713	-4°46'	710	-55.0	224.2
	33°52'	875'	-5°25'	862	-82.5	196.7
	30°40'	752	-5°20' 10.0		-75.4	203.8
	37°10'	750	-6°	738	-78.8	200.4
	39°10'	725'	-6°11'	712	-78.0	201.2
	48°10'	730	-4°05' 8.0	723	-55.5	223.7
	48°35'	570	-6°11' 10.0	566	-65.8	213.4
	55°50'	770	+0°25'	770	-5.6	273.6
	52°20'	543	-7°25'	534	-69.4	209.8
	52°55'	648	-4°38' 7.0	637	-53.5	225.7
	52°30'	533'	-7°36'	520	-70.3	208.9
	60°47'	436'	-7°50'	427	-59.2	220.0
	71°45'	354'	-8°52'	346	-54.3	224.9

Elev. 279.2

Station	Az.	Stadia	V Δ	Hor. D.	Diff. Elev	True Elev
	59°05'	408	-10°10'	395	-70.9	208.3
	64°30'	310	-12°37'	295	-66.3	212.9
	73°50'	283'	-13°51'	267	-66.2	213.0
	94°45'	220'	-17°20'	200	-63.0	216.2
	60°05'	257'	-15°41'	237	-71.0	208.2
℄ ditch	55°	265'	-15°15'	255	-67.2	212.0
	104°20'	312'	-10°54'	301	-58.0	221.2
	45°38'	335'	-11°40'	322	-67.0	212.2
	115°50'	333'	-8°23'	327	-48.2	231.0
	121°35'	276'	-12°20'	264	-58.0	221.2
	129°50'	193	-17°40 9.0	176	-60.2	219.0
	~~143°35~~	295	11.0			
	90°20'	487'	+6°17'	481. ~~432~~	53.0 ~~+58.1~~	332.2 ~~337.3~~
	137°20'	367'	-6°44'	360	-42.8	236.4
	90°	565'	+8°55	548	+87.0	366.2
	143°10'	335'	-8°50'	328	-51.0	228.2
	140°0	260'	-13°05'	246	-58.0	221.2
	93°10'	617	+10°18' 8.0	595	111.0 ~~+105.0~~	390.2 ~~384.2~~
	96°27'	598'	+9°58'	577	+102.0	381.2
	102°05'	585'	+9°44'	568	+97.6	376.8

Station	Az.	Stadia	V Δ	Horiz D.	Diff. Elev	True Elev.
Head of Ridge	104°50'	585'	+9°36'	~~569~~ 561	+ 97.0	376.2 ✓
Hd of Draw	105°20'	595'	+9°33'	~~579~~ 576	+ 98.0	377.2 ✓
	107°20'	605'	+9°15'	589	+ 96.5	375.7 ✓
	127°15'	405'	-4°05'	403	- 28.5	250.7 ✓
	111°0'	765'	+8°05'	~~750~~ 740	+ 107.0	386.2 ✓
	114°45'	795'	+7°55'	~~780~~ 778	+ 108.0	387.2 ✓
Draw	128°30'	450'	-2°38'	450	- 20.8	258.4 ✓
Rim	118°45'	860'	+7°54'	~~844~~ 840	+ 117.5	396.7 ✓
	122°20'	790'	+7°53'	775	+ 107.5	386.7 ✓
	125°20'	774'	+8°15' 9.0	758	+ 107.0	386.2 ✓
Draw	125°20'	485'	-1°13'	485	- 10.7	268.5 ✓
	117°50'	786	+7°12' 11.0	~~774~~ 770	+ 92.0	371.2 ✓
Draw	119°25'	737	+5°31' 7.0	730	+ 69.2	348.4 ✓
Draw	119°35'	706	+5°00' 11.0	701	+ 55.8	334.0 ✓
"	121°45'	543	+0°52' 8.0	543	+ 5.5	284.7 ✓
"	118°50'	660	+4°20' 13.0	656	+ 41.9	321.1 ✓
"	120°20'	590	+1°28'	590	+ 14.8	294.0 ✓
	116°40'	674	+5°07' 14.0	669	+ 51.3	330.5 ✓
	117°0'	700'	+5°48'	698	+ 70.8	350.0 ✓
	115°40'	737	+7°10' 6.0	726	+ 90.5	369.7 ✓
	114°23'	770'	+7°50'	757	+ 104.0	383.2 ✓

station	Az	Stadia	V/A	H.D.	V.D.	Elev.	
	124°25'	615'	+3°17'	612	+34.8	314.0	✓
	109°20'	674'	+9°05' 11.0	657 ~~681~~	+ 100.0	379.2	✓
	108°38'	693'	+9°03'	627	+ 99.5	378.7	✓
	128°05'	586'	+3°25' 7.0	584	+ 33.0	312.2	✓
	107°45'	590'	+8°54'	575	+ 90.5	369.7	✓
	181°25'	537'	+2°45'	537	+ 24.8	304.0	✓
	110°45'	536'	+6°50'	528	+ 63.5	342.7	✓
	130°30'	513'	+1°25'	513	+ 12.8	292.0	✓
	113°55'	485'	+4°25'	483	+ 37.2	316.4	✓
	133°55'	627'	+2°16'	525	+ 21.0	300.2	✓
Drow	108°15'	464'	+4°09	461	+ 33.8	313.0	✓
	137°33'	545'	+2°50'	544	+ 36.2	315.4	✓
	104°15'	467'	+5°21' 7.0	462	+ 41.2	320.4	?
	135°55'	608'	+5°24'	600	+ 57.0	336.2	✓
	134°45'	683'	+7°20'	672 ~~667~~	+ 87.2	366.4	✓
	99°38'	463'	+4°06' 6.0	462	+ 32.2	311.4	✓
	132°17'	774'	+8°05' 11.0	759	+102.0	381.2	✓
	96°30'	465'	+3°35'	462	+ 29.2	308.4	?
	129°27'	730'	+8°04'	715	+ 102.0	381.2	✓
	88°27'	461'	+4°35'	459	+ 37.0	316.2	✓

Station	Az.	Stadia	V Δ	H. D	D. El.	Elev
	123°42'	775'	+7°47'	~~761~~ 755	+ 104.0	383.2 ✓
	83°36'	500'	+4°19'	496	+ 37.8	317.0 ✓
	81°15'	515'	+4°05'	512	+ 36.8	316.0 ✓
Ridge Rim	80°35'	595'	+7°23'	586	+ 76.0	355.2 ✓
Draw	120°40'	773'	+6°21'	765	+ 86.0	365.2 ✓
	74°20'	574	+5°27' 11.0	568	+ 48.0	327.2 ✓
	~~121°05'~~	~~727~~	~~+5°25'~~	~~720~~	~~+ 68.3~~	~~347.5~~ ✓
	69°35'	585	+3°15' 10.0	582	+ 28.0	307.2 ✓
	62°50'	563	-0°36'	563	- 6.3	272.9 ✓
	121°15'	706	+6°05' 10.0	~~699~~ 695	+ 70.0	349.2 ✓
	58°45'	557'	-2°15' 11	556	- 27.8	251.4 ✓
	55°00'	553	-5°30'	549	- 53.0	226.2 ✓
	122°10'	677'	+5°36'	670	+ 66.8	346.0 ✓
	53°05'	526'	-7°55'	516	- 73.0	206.2 ✓
	125°10'	670	+5°20'	663	+ 62.2	341.4 ✓
	127°33'	615'	+4°12'	610	+ 45.0	324.2 ✓
Side Hill ditch	96°.	395'	-1°40'	395	- 11.4	267.8 ✓
	128°30'	525'	+1°30'	525	+ 13.8	293.0 ✓
	92°30	384'	-1°26'	384	- 9.7	269.5 ✓
	131°48'	496'	+1°08'	496	+ 9.6	288.8 ✓

Station	Az.	Stadia	V.A.	H.D.	V.D.	Elev.	
	96°20'	343'	-8°12'	335	- 47.2	232.0	✓
	136°10'	475'	-1°15'	475	- 10.5	268.7	✓
	146°20'	487'	-2°56'	485	- 33.2	246.0	✓
drain	115°26	363'	-5°22'	360	- 34.0	245.2	✓
	150°45'	523'	-2°13 10.0	523	- 25.3	253.9	✓
	154°0'	590'	0°	590	= 0.0	279.2	✓
	118°20'	437'	+0°35	437	+ 4.5	283.7	✓
	157°50'	535'	-4°13'	~~537~~ 537	- 39.3	239.9	✓
	114°43'	470'	+3°29'	463	+ 28.7	307.9	✓
	154°15'	446'	-6°08'	440	- 47.8	231.4	✓
	146°20'	456'	-4°48'	452	- 38.2	241.0	✓
	113°0	600'	+6°21' 12.0	~~587~~ 593	+ 59.3	338.5	✓?
	139°45'	427'	-5°22'	422	- 40.0	239.2	✓
	134°50'	420'	-4°37'	417	- 34.0	245.2	✓

Walker
Hendricks
Becker
Greer
11-25-46

Levels Existing Paving on Montezuma Road

	549	278.25			BM.
	~~549~~	~~277.25~~		272.76	
		266.53		265.62	
T.P.	0.91	~~265.53~~	12.63	~~264.62~~	
0+00			6.06	60.47	9' Lt of Painted Stripe
1+00			10.82	55.71	
T.P. #1	1.20	255.21	12.52	254.01	3.5' Lt of Stripe
		~~254.21~~		~~253.01~~	1' Lt of
2+00			3.67	51.59	Stripe
3+00			8.17	47.04	
T.P.		247.20		242.77	
4+00	4.43	~~246.20~~	12.44	~~241.77~~	
3+57.4					
44.6' Rt on Hdwall			10.98	36.22	
" " " Flow 24"		culvert	15.68	231.52	
5+00			8.88	38.32	
Hub ⊙	Last Hub West of 5+45.5		2.44	237.76	238.0 -
		236.91		236.76	
TP	1.82	~~235.91~~	12.11	235.09	
				~~234.09~~	
6+00			3.37	33.54	
7+00			7.95	28.96	
+30			9.36	27.55	
+50			10.17	26.74	
		247.66		236.04	
TP	11.62	~~246.66~~	0.87	~~235.04~~	

Cont. P-24



Montezuma Road

Cont. from P-23

		24766		
		~~247.66~~		
		259.82		246.92
T.P.	12.90	~~258.82~~	0.74	~~245.92~~
		271.12		258.91
T.P.	12.21	~~270.12~~	0.91	~~257.91~~
		280.91		269.84
T.P.	11.07	~~279.91~~	1.28	~~268.84~~
		West of		277.14
Mo.6	⊙ 51+45.5		3.77	~~276.14~~ ✓
				272.76
chk Mo.6	51+45.5		8.15	~~272.76~~
		26882		268.30
T.P.	0.52	~~267.82~~	12.61	~~267.30~~
				265.61
chk TP#1 P-23			3.21	~~264.61~~
				265.62
				0.01

54th St. Extension
Base Line Ties to Collwood-
- Subdivision



Walker
Hendricks
Becker
Greer
11-27-46

54th St. Ext.
Ties to Base Line



Station	Align.	Deflection Lt	Deflection Rt.	Col. Bearing	Mag. Bearing
4+00		$8°27\frac{56}{}$			
			$\Delta_c - 35°50'$ (17°55)		
3+50		$7°01\frac{61}{}$ ✓	$L_c - 625.41$ ✓		
			$R_c - 1000'$ Lt.		
3+00		$5°35\frac{67}{}$ ✓	$C_c - 615.27'$		
+85	P.O.C.	$5°09.88$	def 1' 1.719 def 50' $1°25\frac{944}{}$		
2+50		$4°09\frac{72}{}$ ✓			
2+00		$2°43\frac{28}{}$ ✓			
1+50		$1°17\frac{84}{}$ ✓			
1+04 $\frac{12}{P.S.C}$	P.S.C	$\frac{0°00'}{1°00}$			
1+00		$0°54'$	$\Delta_3 - 3°00'30'' \quad a - 5.471$		
0+75		$0°30'$	$L_3 - 104.72 \quad x - 104.69$		
0+50		$0°13'$ ✓	$T_3 - 486.63 \quad y - 1.83$		
0+25		$0°03'$ ✓	$C_3 - 104.71$		
L-0+00 $\frac{00}{P.S.}$	P.S.	$0°00'$	$K - 0°06.83895'$		
				N. 4° 30' W.	

B+68 $\frac{24}{}$ Ahd

B+69 $\frac{48}{E.C.}$ Bk

5+0	12°49.92'
4+50	11°23.98'
	$\Delta - 46°50'$ Lt.
	$R - 1000'$
	$T - 433.08$
	$L - 817.40$
+20	10°32.42'
4+0	9°58.04'
+70	9°06.47'
+45	8°23.50'
+25	7°49.12'
3+0	7°06.15'
+85 P.O.C.	6°40.36'
+50	5°40.20'
2+0	4°14.26'
+50	2°48.31'
1+0	1°22.37'
0+52 $\frac{08}{B.C}$	

B+ 3+09.93

See page 16 for the 100 R-1 inc.

0+00

Station	Align.	Deflection Lt.	Deflection Rt.	Cal. Bearing	Mag. Bearing
9+00		3° 46'	Δ_s - 8°00'		X - 278.71
+75		3° 19'	L_s - 279.25		Y - 12.98
+50		2° 49'	T_s - 574.02		
+25		2° 17'	a - 2.052		
8+00		1° 43'	C_s - 279.01		
~~2+82.79~~	~~P.T.S~~	1° 06'	k - 0° 02.038		
+50		0° 26'	def.l - 1.719		
7+30	P.C.S	0° 00' / 17° 55'			
		51			
7+00		17° 03			
6+50		15° 37			
6+00		14° 11			
5+50		12° 45			
5+00	P.O.C.	11° 19			
4+50		9° 53			

4+37.51 P.O.T

8+68.44		
8+69.48	P.C.	23° 25'
+50		22° 51.53'
8+0		21° 25.58'
+50		19° 59.64'
9+0		18° 33.70'
+50		17° 07.75'
6+0		15° 41.81'
+75		14° 58.84'
+55		14° 24.96'
+40		13° 58.67'
5+25		13° 32.89'

Station	Align.	Deflection Lt.	Deflection Rt.	Cal. Bearing	Mag. Bearing.
+75	Δ_s - 7°09'		1° 10'		
+50	L_s - 299.50		0°-55'		
+25	T_s - 496.17'		0°-41'		
13+00	C_s - 299.29		0° 29' ✓		
+75	Q - 1.594		0° 19'		
+50	K - 0° 0.7898		0° 12' ✓		
+25			0° 06'		
12+0.05	P.S.		0° 02' ✓		
+75			0° 00 16		
11+65 09 P.S	P.S	0°00'	0°00'		
				N. 51° 20' W.	
+09 38	P.T.	5° 20'			
10+00		5° 08'	5° 08'		
+75		4° 51'	4° 51		
+50		4° 32'	4° 32		
9+25		4° 10'	4° 10'		

1555.91
296.65

Station	Align.	Deflection Lt.	Deflection Rt.	Cal. Bearing	Mag. Bearing
18+38.09	P.C.S		8° 55'		
30.91			54.54		
18+00			8° 00.46		
			(8° 55')		
+50	Δc - 17° 50'		6° 48.81		
	Rc - 1200' Rt.				
17+00	Lc - 373.50'		5° 37.19		
	def. 1' - 1.432'				
+50	def. 50' - 1° 11.62'		4° 25.37		
	L. Chord 371.99				
16+00			3° 13.95		
+50			2° 02.33		
15+00			0° - 50.71		
35.41					
			00° 00'		
14+64.59	P.S.C.		2° 23		
19.59					
+50	[illegible]		2° 10'		
+25	[illegible]		1° - 48'		
14+00	[illegible]	[illegible]	1° - 28'		

Δ - 32° 08' Rt.

Station	Align	Deflection Lt.	Deflection Rt	Cal Bearing	Mag. Bearing
	1/184.46			N. 19 12' W.	
+37 59 / 12.59	P.T.		4° 46'		
+25			4° 27 07		
21+00	Δ_3 - 2°09'		4° 11 00		
+75	L_3 - 299.50'		3° 52 98		
+50	T_3 - 496.17'		3° 32 96		
+25	C_3 - 299.29'		3° 10 94		
20+00	a - 1.594		2° 46 92		
+75	K - 0° 00 29'		2° 20 90		
+50			1° 52 88		
+25			1° 22 86		
19+00			0° 50 84		
+75			0° 16 82		
+50					
18+38 09 / PC 3	P.C.S	1.91	0° 00' / 8° 55		

def 1' - 1.432
def 25 - 0° - 35 81

N. 19°12

2184.46

Station	Align	Deflection Lt.	Deflection Rt	cal Bearing	Mag. Bearing
	Rt. leg of Wyec.				
+50	Δ_c - 46°51'		6° 07 99		
	Rc - 600'				
47 -	Lc - 490.61'		3° 44 75'		
	def.1' - 2.865'				
	def.50' - 2° 23 24				
+50			1° 21 51		
	28.45				
			0° 00'		
+21 55	P.S.C.		4° 46'		
46 +00			4° 07 09		
+75	Δ_s - 14°18'		3° 24 63		
+50	L_s - 299.50'		2° 46 17		
+25	T_s - 589.08'		2° 11 71		
45 +00	C_s - 298.67		1° 47 25		
+75	a - 3.188'		1° 14 79		
+50	K - 0° 04 46'		0° 52 33		
+25			0° 33 87		
44 +00			0° 19 41		
+75			0° 08 95'		
+50			0° 2 49		
	27.95				
43 +22 05	P.S.		0° 00'		

Δ - 71° 54' Rt.

Station	Align	Deflection Lt.	Deflection Rt.	Cal. Bearing	Mag. Bearing
				N. 52° 42' E.	
+12 16	P.C.S		0° 00'		
			23° 25 30		
			34 83		
51 +00			22° 50 67		
+50			20° 27 43		
50 +00			18° 04 19		
+50			15° 40 25		
49 +00			13° 17 21		
+50			10° 54 47		
48 +00			8° 31. 23		

+37 31	P.I. 12.31	7°-10'
+25	Δ_S - 10°45'	7°-01 73
53+00	L_S - 225.15	6°-31 64
+75	T_S - ~~550.12~~ 552.96	5°-56 38
+50	C_S - 224.80'	5°-15 98
+25	a' - 4.241	4°-30 33
52+00	K - 0°02.723	3°-39 54
+75		2°-43 58
+50		1°-42 40
+25		0°-36 09
51+12 16	P.C.S 12.85	0°00'
		23°25 50

def. 1' - 2.865
" 25' - 1°11 62

Station	Align	Deflection Lt.	Rt.	Cal. Bearing	Mag. Bearing
		Lt. leg of wycc.			
+50		4° 59 40		Δ_c - 53° 05'	
				R_c - 750' Lt.	
46+00		3° 05 37		L_c - 694.86'	
				def 1' 2.292	
				def 50' 10 54.592"	
+50		1° 10 28			
	30.88				
+19 12	P.S.C.	0° 00' / 3° 30			
45+00		3° 02 29			
+75		2° 28 24		Δ_s - 10° 30'	
+50		1° 58 49		L_s - 274.89'	
+25		1° 31 24		T_s - 706.42'	
44+00		1° 07 89		C_s - 274.48'	
+75		0° 47 84		a - 2.779	
+50		0° 31 29		K - 0° 00 80'	
+25		0° 18 23			
43+00		0° 08 69			
+75		0° 02 64			
+50	5.22	0° 00 03			
42+44 23	P.S.	0° 00'			

N. 19° 12' W.

Δ - 74° 05' Lt.

Station	Align.	Deflection Lt.	Deflection Rt.	Cal. Bearing	Mag. Bearing
+50		24° 05 $\frac{86}{}$			
51+00		22° 11 $\frac{27}{}$			
+50		20° 16 $\frac{68}{}$			
50+00		18° 22 $\frac{09}{}$			
+50		16° 27 $\frac{50}{}$			
49+00		14° 32 $\frac{91}{}$			
+50		12° 38 $\frac{32}{}$			
48+00		10° 43 $\frac{73}{}$			
+50		8° 49 $\frac{14}{}$			
47+00		6° 54 $\frac{55}{}$			

S. 86° 43' W.

+88 87	P.T.	7° 00'	
+75		6° 47 42	Δ_s + 10° 30'
+50		6° 25 19	L_s + 274.89
+25		5° 59 48	T_s - 706.47
54 +00		5° 29 56	C_s - 274.48
+75		4° 56 54	a - 2.779
+50		4° 20 02	K - 0° 01 53
+25		3° 40 00	
53 +00		2° 56 48	
+75		2° 09 46	
+50		1° 18 94	
+25		0° 24 92	
		0° 00'	
+13 98	P.C.S	26° 32 50	
	11.02'		
		def. 1'	2.292
52 +00		def. 25'	0° 57.296
		26° 00 45	

Alignment Proposed Through Hwy
West of 54th St. El Cajon Blvd to Montezuma Road.
"L" Line

3+0		7°06.15'	
+85	P.O.C.	6°40.86'	
+50		5°40.20'	
			Δ 46°50'
2+0		4°14.26'	R 1000'
			T 433.08
+50		2°48.31'	L 817.40
			D 1.719
1+0		1°22.37'	
0+52.08	B.C.Lt.		
			N. 5°35'10" W
0+00			

Jan 6 47
Sisson
McCoy
Waddell
Hilton
Mark Order 175

N. 52°25'10" W.
46°50'
7°13'
3+09.93 P.O.S.T.
Fd Hub
N. 5°35'10" W.
N. 80°24'00" W.
33°00'00"
54 1/4 St.
N. 5°35'10" W.
N 81°27' E
Fd Hub
0+52.08 B.C.Lt.
10°55'
7°13'
0+15.63
85°23'
0+00
Fd Hub
Set Roofstack
El Cajon Blvd.

2° L.T.C.

+55		14°24.46'
+40		13°58.67'
+25		13°32.89'
5+10	P.O.C.	12°49.92'
+50		11°23.98'
+20		10°32.42'
4+10		9°58.04'
+70		9°06.47'
+45		8°33.50'
3+25		7°49.12'

2" Line

11+65.09	P.O.T.		N. 52° 25' 10" W.
8+68.44 AHD = 8+69.48 BK	E.C.	25°25'	
+50		22°51.53'	
8+0		21°25.58'	
+50		19°59.64'	
7+0		18°33.70'	
+50		17°07.75'	
6+0		15°41.81'	
5+75		14°58.84'	

2" Line

17+0		10°48.27'	
+50		9°36.65'	
16+0		8°25.03'	
+50		7°13.41'	
			Δ 38°13'20"
15+0		6°01.79'	D 12°00'
			T 357.96
+50		4°50.17'	L 695.75
			D 1.4324
14+0		3°38.55'	
+50	P.O.C.	2°26.93'	
13+0		1°15.31'	
12+47.42	B.C. Pt.		

378.98



Jan. 19-46
Sisson
Riddell
Allen

L L Line

26+62.59	P.O.T		
23+09.55	P.O.T.		
			N. 19° 12' W.
20+84.64	P.O.T		
19+43.17	E.C.	16° 38.58'	
19+0		15° 34.75'	
+50		14° 33.13'	
18+0	P.O.C.	13° 11.51'	
17+50		11° 59.89'	

19+43.17 E.C.

2" Line

N. 19°12' W.

46+40.00 P.O.T.

42+50.00 P.O.T.

39+36.96 P.O.T.

37+299.00 P.O.T.

36+29.35 P.O.T.

32+78.12 P.O.T.

"L" Line

48+00		15° 55.71'	
+50		13° 12.47'	
47+00		10° 49.23'	
+70	P.O.C.	9° 23.29'	
+75		8° 26'	Δ 71° 54' 30"
			R 600'
46+00	P.O.C.	6° 02.75'	T 435.19
			L 753.02
+50		3° 39.51'	D 2.86478
+25		2° 27.89'	
45+0		1° 16.27'	
44+73.88	B.C.R.L.		

25 30.21

24" Conc. Pipe Culvert

9" Cobble Headwall

53+78.18

53+00.37 E.C.

T 49+82.87

Δ 33° 40'

R ~~1200~~ (1198.40) To Balance

T ~~363.06~~ 362.58

L ~~705.41~~ 704.17

11+94.96 E.C.

11+19

52+36.40 E.C.

℄ Montezuma Road ℄

48.22

Fd Hub

T.-1.

Δ 74° 25' 30"
R 638.58
T 483.41
L 829.89
D 2.70016

Δ 71° 54' 30"
R 600
T 435.19
L 753.02
D 2.86478

44+73.38 B.C.L.L.

44+73.38 B.C.R.L.

"L" Line

N. 52° 42' 30" E.

+26.10	F.C.	35° 57.25'
52+0		34° 41.63'
+50		32° 18.89'
51+0	P.O.C.	29° 55.15'
+50		27° 31.91'
50+0		25° 08.67'
+50		22° 45.43'
49+0	P.O.C.	20° 22.19'
48+50		17° 58.95'

Alignment L' Line

Sketch Page 46 Levels #1237-18

+50		21° 26.95'	
+25		20° 19.44'	
49+0		19° 11.94'	
+75		18° 04.43'	
+50		16° 56.93'	
+25		15° 49.43'	
48+0		14° 41.92'	
+75		13° 34.42'	Δ 74° 25' 30"
+50		12° 26.91'	R 636.58
+25		11° 19.41'	T 483.41
47+0	P.O.C.	10° 11.91'	L 826.89
+65	P.O.C.	8° 37.40'	D 2.700
+25		6° 49.39'	
46+0	P.O.C.	5° 41.89'	
+75		4° 34.39'	
+50		3° 26.88'	
+25		2° 19.38'	
45+0		1° 11.87'	
44+73.38	B.C. L'		

"4"

53+00.27	E.C.	37° 12.25'
+75		36° 04.49'
+50		34° 57'
+25		33° 49.48'
52+0		32° 42'
+75		31° 34.48'
+50		30° 27'
+25		29° 19.47'
51+0		28° 12'
+75		27° 04.47'
+50		25° 56.96'
+25		24° 49.46'
50+0		23° 41.95'
49+75		22° 34.45'

Indexed
O.S.K.

Cross Section "L" Line
Proposed Through Way West of 54th St.
El Cajon Blvd. to Montezuma Road

Alignment Page 40-49

1+50 30' Lt of ℄ = Woven Wire Fence

Note:- From Sta. 0+0 to 18+0 Regular Sections
18+50 to End Rt + Lt. + above ℄ - below ℄

1+0

0+52.08 B.C. Lt. 45' Lt of ℄ = Woven Wire Fence

0+063 = N.L. of El Cajon Blvd Paving Taken on Diag

0-03.4 = N Cb Line of El Cajon Blvd Taken on Diag

BM 3.69 407.46 405.77 S.F.B.R. El Cajon & 54th St.

Sep. 22-47
S.S.S.O.7
McCoy
Waddel
Allen
Green

50

Lt = W

℄

Rt = E

401.3	402.1	402.4	402.1	402.2	401.4	402.1	401.4	402.2	402.7			
63	54	51	54	53	61	54	61	53	48			
50	36	13	16		1	24	39	42	50			
402.1	402.3	402.9	402.1	402.2	402.4	402.2	403.4					
54	53	46	54	53	51	53	41					
50	47	7	5		20	35	16=Wire Fence					
402.3	402.6	402.9	402.3	402.5	402.9	402.88	405.07					
52	49	46	52	50	41	38	239					
50	36	10	9		20	39=W.W.F.	50=P.C. Pav.					
						Paving						
401.0	401.9	402.25	401.75	402.68	403.81	404.23	404.77	405.37				
65	56	52	59	478	365	323	269	209				
30	30	14=Cb.	14=Gutter		20	379=Gutter	379=Cb	50=W.Y. Conc Walk				
400.00	399.41	401.80	401.83	402.64	403.67	404.29	403.92	405.53				
746	805	605	563	483	379	317	254	193				
66=Cb	65=Gutter	33½=Cb & Gutter	14		20	38	258=Gutter	58=Cb & Gutter				

407.46

| | | |

	Lt.			Rt	
5+25	373.2	387.3	385.9	392.5	394.3	396.7
	24.0 / 75	14.9 / 50	11.3 / 30	4.7 / 20	2.9 / 33	0.5 / 50
5+0	365.7	373.4	382.7	388.7	395.6	396.6	397.2
	21.5 / 100	23.8 / 75	14.5 / 50	7.5 / 25	1.6	0.6 / 25	0.0 / 50
4+50	364.2	365.9	378.2	388.4	395.9	396.6	397.4	398.0
	22.0 / 110	21.3 / 90	19.0 / 60	8.8 / 25	1.3 / 6	0.6	+0.2 / 25	+0.8 / 50
4+20	366.4	367.0	375.9	384.2	391.4	397.0	398.3
	30.8 / 100	30.2 / 80	21.3 / 50	13.0 / 22	5.8	0.2 / 18	+1.1 / 50
4+0	370.2	368.5	359.7	368.2	386.1	391.0	397.8	398.2
	27.0 / 90	28.7 / 76	27.5 / 55	19.0 / 25	11.1	6.2 / 33	+0.6 / 38	+1.0 / 50

399.17

399.17

2" Line

						Lt.		℄		Rt.	
						353.3	356.3	360.4	367.3	375.3	384.4	388.7	394.9	395.4
						34.1 100	31.1 75	27.0 50	20.1 25	12.1	3.0 25	+1.3 40: Toe Hor Fill	+7.5 53: Top Fill	+8.0 70
6+50														
						355.0	357.0	360.4	367.2	374.9	385.2	391.9	395.9	396.3
6+25						32.4 100	30.1 75	27.0 50	20.2 25	12.5	2.2 25	+4.5 50	+8.5 61	+8.9 70
							362.1	363.4	352.9	374.0	383.4	388.4	396.2	
6+0							25.3 85	24.0 64	24.5 37	13.4	4.0 25	+1.0 50	+8.8 70	
						369.0	373.1	371.8	371.4	375.0	380.0	390.1	396.6	
5+75						18.4 80	14.2 50	15.6 25	16.0 9	14.4	7.4 20	+2.7 45	+9.2 70	
										387.41				
TP	2.55	387.41	12.31	384.86	on Post 5+45 Lt									
						373.1	379.4	380.7	380.1	381.4	389.4	393.8		
5+55						24.1 75	19.8 43	16.5 25	17.1	15.8 25	7.8 43	3.4 60		
		397.17								397.17				

	Lt.			℄			Rt.	
8+50	341.6	350.4	357.6	344.4	371.0	376.3	382.3	384.3
	4.58	5.70	2.98	2.30	16.4	11.1	5.1	3.1
	100	75	50	25		25	50	75
8+0	346.1	353.0	359.3	367.5	375.2	380.2	384.5	389.1
	4.13	3.41	2.81	1.99	12.2	7.2	4.9	+1.7
	100	75	50	25		25	50	75
7+75	346.4	352.8	359.1	367.4	376.7	382.1	388.1	393.9
	4.10	3.46	2.83	2.02	10.7	5.3	+0.7	+6.5
	100	75	50	25		25	50	75
7+50	346.6	351.4	358.3	366.3	374.4	380.7	386.2	393.9
	4.08	3.60	2.91	2.11	13.4	6.7	1.2	+6.5
	100	75	50	25		30	50=Top Nom Fill	70=Top Nom Fill
7+0	350.2	352.4	359.3	365.0	372.0	382.2	394.7	395.1
	3.72	3.50	2.81	2.24	15.4	5.2	+7.3	+7.7
	100	75	50	25		30=Top Nom Fill	55=Top Nom Fill	75

387.41

387.41

					Lt.		Rt.			
10+00					333.9	337.7	340.3	343.6	347.2	350.1	346.4	342.6
					180	142	116	83	47	18	55	95
					100	75	50	25		20	50	80
					Ely Ways							
TP	0.11	351.88	12.12	351.77				351.88				
9+70					335.2	340.0	343.6	348.1	355.8	360.1	360.0	356.0
					287	239	203	158	81	88	39	79
					100	75	50	25		25	46	70
TP	0.50	363.89	12.99	363.39				363.89				
9+45					338.1	343.0	347.4	353.2	361.0	364.4	378.0	365.6
					283	234	190	132	154	120	84	108
					100	75	50	25		12	50	75
9+0					340.5	346.4	353.3	360.4	366.8	373.4	376.9	376.4
					159	100	221	160	96	130	+0.5	00
					100	75	50	25		25	50	75
TP	1.15	376.38	12.18	375.23				376.38				
8+68.47					341.7	348.2	355.9	363.7	371.8	377.0	381.6	382.3
8+69.48	= EC				457	392	415	227	156	104	54	151
					100	75	50	25		25	50	75
		387.41						387.41				

2" Line

						Lt.				Rt.		
11+77	For Profile	14.5		= Bottom Plate		327.4	329.7	328.9	328.6	326.6	327.8	325.5	325.4	326.5	330.6	337.3
						12.4	10.1	10.9	11.2	13.2	12.0	14.2	14.1	13.3	9.2	3.5
11+65				14.6		8.7	7.5	6.0	3.6	2.5		5	1.8	4.4	5.0	7.5
				9.1 = Bottom Plate												
						325.3	325.4	331.2	330.9	330.0	329.8	330.3	330.4	330.6	328.3	
11+35						14.5	14.4	8.6	8.9	9.8	10.0	9.5	9.2	9.2	11.5	
						9.0	8.2 = Bottom Plate	7.3	6.0	2.5		2.5	5.2	7.5	9.1 = Bottom Plate to Lat	
						326.7	331.3	332.4	332.6	331.4	330.8	331.6	331.9	332.6	332.8	
11+0						12.1	8.5	7.4	7.2	8.4	9.0	8.2	7.9	7.2	7.0	
						10.0 = Bottom Plate	9.0	7.5	5.0	2.5		2.5	5.0	7.5	10.0	
BM #68			14.8°	338.04	Page 19 338.03											
						329.9	332.0	333.3	334.8	335.3	334.3	333.6	333.7	333.3	333.9	
10+60						9.9	7.8	6.5	5.0	4.5	5.5	4.2	5.1	4.5	5.9	
						10.0 = Bottom Plate	9.0	7.5	5.0	2.8		2.5	5.0	7.5	10.0	
TP	0.83	339.84	12.87	339.01							339.84					
						332.1	334.9	336.8	338.8	340.0		338.4	336.7	335.3	334.8	
10+35						19.8	17.0	15.1	13.1	11.9		13.5	15.2	16.4	17.1	
						10.0 = Bottom Plate	8.5	5.0	2.5			2.5	5.0	7.5	10.0	
		351.88									351.88					

TP	3.51	333.94	9.44	330.40
13+00				
12+75				
12+47.42	B.C. Rt.			
12+10				
11+83				

325.1
14.7
8 - Bottom Marks

339.84

Lt. | ℄ | Rt.

323.8 / 318.8 / 322.8 / 324.7 / 327.4 / 332.12 / 337.4 / 341.7 / 347.8
16.0 / 21.0 / 17.3 / 15.1 / 12.4 / 7.6 / 2.4 / +1.9 / +8.0
90 / 75 Bottom Marks / 65 / 50 / 25 / / 2.6 / 50 / 75

314.8 / 322.8 / 319.4 / 324.8 / 329.2 / 332.8 / 338.1 / 346.3 / 352.6
15.0 / 17.0 / 20.4 / 15.0 / 10.6 / 7.0 / 1.7 / +6.5 / +12.7
85 / 70 / 61 Bottom Marks / 50 / 25 / / 25 / 50 / 75

325.8 / 324.2 / 321.0 / 324.9 / 329.7 / 333.32 / 339.6 / 348.2 / 354.7
14.0 / 15.6 / 18.8 / 14.9 / 10.1 / 6.52 on Hub / 0.4 / +8.4 / +14.9
85 / 66 / 63 Bottom Marks / 46 / 25 / / 25 / 50 / 75

326.6 / 325.2 / 321.4 / 324.5 / 326.4 / 332.4 / 334.2 / 336.3 / 338.6 / 341.6 / 345.8 / 347.7
12.2 / 14.6 / 18.4 / 15.3 / 13.4 / 7.4 / 5.6 / 3.5 / 1.2 / +1.7 / +6.0 / +7.9
77 / 61 / 54 - 54.0 of 12 Marks / 46 / 25 / / 8 / 14 / 32 - HH Road / 40 / 70 / 75

325.2 / 327.4 / 324.1 / 324.0 / 324.7 / 330.10 / 335.2 / 339.2 / 342.6 / 346.8
11.6 / 12.4 / 13.7 / 15.8 / 15.1 / 9.8 / 4.6 / 0.6 / +2.7 / +4.0
75 / 60 / 28 / 24 / 6 - Bottom Marks / / 25 / 46 / 65 / 85

339.84

						Lt.		Rt.	
TP	7.55	328.92	12.37	321.67	on P.C.? 46 Rt of 12 15+50				
						328.6			
15+00						312.4	314.7	314.4	312.4	314.8	317.5	322.6	328.4
						15.3 7.5	21.5 44	19.0 36	19.5 42	21.5 12	19.1	16.4 27	11.3 50	5.5 7.5
							44-Bottom Marsh							5.6
						321.1	313.1	315.6	315.3	313.8	314.7	318.5	342.2	325.8
14+75						12.8 8.0	20.8 50	18.3 48	18.6 25	20.1 12	19.2	15.4 28	11.7 50	8.1 7.5
							50-Bottom Marsh							
							322.3	313.1	316.1	315.7	316.9	320.5	325.5	331.9
14+50							11.6 8.0	20.8 56	17.8 50	18.2 42	17.0	13.4 30	8.4 50	2.0 7.5
								56-Bottom Marsh						
						319.1	318.1	316.7	317.8	318.9	321.2	326.2	333.4	342.3
14+00						14.8 8.5	15.8 7.0	17.2 56	14.1 50	16.0 25	12.7	7.7 25	0.6 50	+ 8.4 7.5
								56-Bottom Marsh			2 Road			
						320.6	317.9	320.7	321.7	323.8	327.2	330.4	339.3	351.4
13+50						13.3 9.0	16.0 80	12.2 7.0	12.2 50	10.1 25	6.7	2.5 25	+5.4 50	+17.5 7.5
							80-Bottom Marsh							
		333.94								333.94				

Jan. 31-46
Sidney
McCoy
Weddel
Hilton

2" Line

	Lt.		Rt.	
	304.5	304.8	306.7	307.4
7+50	21.5 67	24.1 53	22.2 50	21.5 25
	312.5	308.6	307.5	307.6
17+00	16.4 75	20.3 45	21.4 37	21.3 25
	309.9	309.9	308.3	309.5
7+50	19.0 62	19.0 50	20.6 42	19.4 64
	320.0	311.1	309.8	310.9
16+00	8.9 80	17.8 55	19.1 50	18.0 43
	315.1	311.2	314.2	311.2
15+50	13.8 59	17.7 58	14.7 45	17.7 35

Boston Mass.

Boston Mass.

	Rt.	
	311.8	315.8
7+50	21.1 50	21.1 25
	316.9	309.3
17+00	12.0 50	19.6 25
	316.5	311.6
7+50	12.1 50	17.6 25
	319.9	316.6
16+00	9.0 50	12.3 25
	321.5	318.3
15+50	7.4 50	10.6 25

	329.7
7+00	7.8 75
	322.7
17+00	6.4 75
	322.9
7+50	6.0 75
	324.1
16+00	4.8 75
	326.4
15+50	2.5 75

G28.92

G28.92

Regular → POC

18+10 — 18+00 — 17+90 — 17+80 — 17+70 — 17+60 — 17+50 — 17+40 — 17+30 — 17+20 — 17+10 — 17+00 — 16+90 — 16+80 — 16+70 — 16+60 — 16+50 — 16+40 — 16+30 — 16+20 — 16+10 — 16+00 — 15+90 — 15+80 — 15+70 — 15+60 — 15+50 — 15+40 — 15+30 — 15+20 — 15+10 — 15+00 — 14+90 — 14+80 — 14+70 — 14+60 — 14+50 — 14+40 — 14+30 — 14+20 — 14+10 — 14+00 — 13+90 — 13+80 — 13+70 — 13+60 — 13+50 — 13+40 — 13+30 — 13+20 — 13+10 — 13+00 — 12+90 — 12+80 — 12+70 — 12+60 — 12+50 — 12+40 — 12+30 — 12+20 — 12+10 — 12+00 — 11+90 — 11+80 — 11+70 — 11+60 — 11+50 — 11+40 — 11+30 — 11+20 — 11+10 — 11+00 — 10+90 — 10+80 — 10+70 — 10+60 — 10+50 — 10+40 — 10+30 — 10+20 — 10+10 — 10+00 — 9+90 — 9+80 — 9+70 — 9+60 — 9+50 — 9+40 — 9+30 — 9+20 — 9+10 — 9+00 — 8+90 — 8+80 — 8+70 — 8+60 — 8+50 — 8+40 — 8+30 — 8+20 — 8+10 — 8+00 — 7+90 — 7+80 — 7+70 — 7+60 — 7+50 — 7+40 — 7+30 — 7+20 — 7+10 — 7+00 — 6+90 — 6+80 — 6+70 — 6+60 — 6+50 — 6+40 — 6+30 — 6+20 — 6+10 — 6+00 — 5+90 — 5+80 — 5+70 — 5+60 — 5+50 — 5+40 — 5+30 — 5+20 — 5+10 — 5+00 — 4+90 — 4+80 — 4+70 — 4+60 — 4+50 — 4+40 — 4+30 — 4+20 — 4+10 — 4+00 — 3+90 — 3+80 — 3+70 — 3+60 — 3+50 — 3+40 — 3+30 — 3+20 — 3+10 — 3+00 — 2+90 — 2+80 — 2+70 — 2+60 — 2+50 — 2+40 — 2+30 — 2+20 — 2+10 — 2+00 — 1+90 — 1+80 — 1+70 — 1+60 — 1+50 — 1+40 — 1+30 — 1+20 — 1+10 — 1+00 — 0+90 — 0+80 — 0+70 — 0+60 — 0+50 — 0+40 — 0+30 — 0+20 — 0+10 — 0+00

TP 1.87 3/18/11 1268 3/16/11

5286 3/14/11 18+10 POC

5328.92

+50 — Rt + Lt + Above ℄ − Below ℄

+70

19+15

+42.17 E.C.

305.9

304.8

302.2

303.3 301.0 300.7 303.0 301.3 299.6

303.2 303.2 302.7 299.3 298.7

305.2 305.2 302.9 301.3 299.7

307.7 305.8 303.4 301.6 300.4

312.2 310.3 308.4 304.2 310.63

319.6 319.2 317.1 316.7 320.2

327.0

336.4 328.4 330.3 331.1 331.3

340.6 340.3 337.7 337.4 342.0

5328.92 3/18/11

69

						Lt.			Rt.
BM			10.48	302.02	on Hub 21+23.72 P 302.01 Page 13				
TP	7.05	312.50	12.66	305.45		92.4	94.1	94.4	95.4	97.8	305.4	21.3	38.3	54.4
+50						-13.0 113	-11.3 110	-11.0 70	-10.0 44	-7.6 25	12.7	+15.9 36	+32.9 65	+47.0 96
21+10						97.7 -14.9 108	94.2 -17.9 102 - Back Hors	95.7 -16.9 92	99.0 -13.6 63	01.7 -10.9 25	312.6 5.5	25.5 +12.9 27	41.5 +28.9 59	56.8 +44.2 92
+85						00.5 -15.2 129	94.3 -21.4 81	99.5 -16.2 63	05.5 -10.2 25	3/5.68 2.13 on 406	321 +17.0 37	352.8 +34.4 73	46.9 +51.2 114	
+50						02.1 -13.8 132	92.4 -18.1 75	00.4 -15.1 51	06.9 -8.1 25	315.5 2.6	30.3 +14.8 23	45.7 +30.2 64	66.5 +51.0 114	
20+0					01.7 -11.5 110	98.7 -14.5 81	92.6 -15.6 79 - Back Hors	00.0 -13.2 69	99.6 -13.0 49	04.2 -9.0 25	313.2 4.9	24.1 +10.9 21	38.5 +25.3 49	57.5 +44.3 97
		318.11			)						318.11			

	Δ'	Δ-x			
TP	1.12	303.85	1.95	302.73	
+65					
33+25					
+75					
TP	2.81	314.68	0.13	312.37	
+50					
32+0					
		312.50			

Lt.		Δ		Rt	
91.0	89.8	93.4	306.9	23.7	41.9	62.9
-15.9	-17.1	-16.5	-13.5	7.8	+16.8	+35.0	+56.0
112	90	34	33	35	68	103
93.0	90.1	93.2	98.5	314.9	29.4	42.3	61.1
+8.9	-21.8	-18.7	-16.4	2.8	+17.5	+30.9	+49.2
127	93	51	32	32	54	85
93.2	91.4	91.4	00.7	313.0	30.3	39.4	52.0	61.0
-19.8	-21.6	-21.6	-12.3	1.7	+17.3	+26.4	+39.0	+48.0
130	93	65	26	30	44	63	84
				314.68				
90.6	92.6	91.5	00.1	309.4	23.6	38.0	56.0
-18.8	-16.8	-17.9	-9.3	6.1	+14.2	+28.6	+46.6
98	94	45	20	26	52	85
Bottom Hole						
91.6	93.4	93.4	92.3	93.7	303.0	16.4	28.7	43.4
-11.4	-9.6	-9.6	-10.7	-9.3	9.5	+13.4	+25.7	+42.1
108	102	80	50	25	26	48	80
Bottom Hole						
				312.50				

TP	4.29	282.84	1263	278.55	
26+0					
1+50					
25+0					
TP	0.18	291.18	4285	291.00	
1+50					
24+0					92.6 / -7.4 / 122

305.85

	Lt.		℄		Rt.	
	94.1 / +13.8 / 100	85.6 / +4.7 / 57	81.4 / +0.5 / 25	280.9 / 10.3	81.1 / +0.2 / 40	91.7 / +10.8 / 68	08.6 / +27.7 / 102
	81.2 / -1.2 / 76 Bottom Marsh	84.2 / +1.8 / 73	84.2 / +1.8 / 54	82.8 / +0.4 / 25	282.4 / 8.8	83.4 / +1.0 / 10	90.6 / +9.2 / 34	08.3 / +25.9 / 72	17.8 / +35.4 / 100
	84.2 / -4.1 / 85 Bottom Marsh	84.8 / -1.5 / 8	84.8 / -1.5 / 58	84.8 / -1.5 / 27	286.3 / 4.9	92.2 / +11.4 / 39	02.1 / +22.8 / 60	26.2 / +39.9 / 91
				291.18				
	94.0 / +12.7 / 117	85.3 / -1.0 / 55	86.6 / -4.7 / 27	291.3 / 12.5	05.3 / +14.0 / 34	20.7 / +39.4 / 75	39.8 / +68.5 / 128
	89.7 / -10.8 / 97	87.3 / -12.7 / 52	88.4 / -11.6 / 25	90.9 / -9.1 / 23	300.1 / 3.8	20.6 / +20.6 / 42	39.1 / +39.1 / 74	58.0 / +58.0 / 92

305.85

1+80					
1+50					
1+25					
27+10					
1+68	For Profile		5.1	77.4	
1+62.59	P.O.T.		5.05	77.79	on ℄ Hub
26+50					
		282.84			

		℄		℄		℄		64
	102.4		93.6		18.1			
	+28.2 95		+19.4 66		+2.9 27	8.6	+0.5 26	-4.0 36 - Bottom Mark	-0.6 42	-1.5 80	+5.6 106
	102.1	90.4	74.9	73.0	74.9	275.2	74.2	71.2	74.8	74.8	86.6
	+27.5 94	+15.2 63	-0.3 26	-2.2 23	-0.3 20	7.6	-1.0 10	-4.0 11 - Bottom Mark	-0.4 43	-0.4 57	+11.4 114
	300.2	83.5	75.2	73.6	75.5	276.6	71.9	76.0	79.5	91.8	
	+33.6 92	+6.9 48	-1.4 12	-3.0 10	-1.1 8	6.2	-4.7 14 - Bottom Mark	-0.6 21	+2.9 53	+15.2 112	
	98.0		80.9		76.0	274.2	77.6	81.8	98.9		
	+23.8 91		+6.2 40		+1.8 6	8.6	+3.4 15 - Bottom Mark	+7.6 53	+21.5 102		
	96.2	83.6	80.2		77.1	277.1	82.2	93.1	111.2		
	+17.5 101	+4.9 46	+1.5 20		-1.6 12	4.1	+2.5 43	+15.0 82	+32.5 116		
			282.84								

						Lt.			Rt.		
						16.8	07.9	88.7	276.7	68.3	66.3	64.3	67.8
+50						+10.1 100	+3.5 77	+12.0 32	61	-8.1 23	-10.4 58	-12.4 82	-8.9 81
											272.1 -4.6 111	Bottom Hole	
+08	For Profile		12.0	70.8		08.1	85.8	79.6	267.2	67.5	68.2	65.7	68.8	74.8
29+0						+10.9 85	+18.6 41	+12.4 12	15.1	+0.3 10	+1.0 40	-1.5 43	+1.6 52	+7.6 105
									Bottom Hole			Hole Water		
+75	For Profile		14.9	67.9		18.6	99.9	81.9	273.2	68.0	70.4	67.8	70.6	75.8
+62						+15.4 105	+22.7 69	+8.7 35	9.6	-5.2 13	-2.8 47	-5.9 33	-2.6 17	+2.6 77
										Bottom Hole			+8.4 104	281.6
						12.6	90.0	81.0	277.1	71.2	68.4	71.1	71.5	83.5
+40						+35.5 111	+12.9 57	+4.9 31	5.7	-5.9 25	-8.7 30	-6.0 38	-2.6 63	+6.4 109
											Bottom Hole			
						01.3	82.5	82.0	277.7	73.5	69.4	72.9	75.7	
28+0						+23.6 88	+11.8 53	+4.3 28	5.1	-4.2 35	-8.3 38	-4.8 50	-2.0 100	
											Bottom Hole			
		282.84							282.84					

						Lt.			Rt.	
TP	12.47	307.46	0.19	294.99						
					317.2	307.2	300.2	291.4	278.2	269.9
+25					+27.1 118	+17.1 64	+10.1 61	5.1 −5.8 28	−14.9 64	−22.2 99
					330.9	305.9	300.9 289.4	282.1	276.2	270.2 267.7
31+0					+41.5 122	+16.5 58	+11.5 37	5.8 −7.3 32	−13.2 62	−19.2 89 −21.7 99
					330.6	318.9	304.7	289.2 283.1	277.5	264.7 273.1
+75					+41.4 97	+29.7 63	+16.5 40	6.0 −6.1 22	−11.6 46	−24.5 90 −16.1 129
					333.6	315.6	298.7	305.4	273.1	264.1 265.2
+50					+48.2 104	+30.2 66	+13.3 30	9.8 −7.8 22	−12.2 49	−21.3 72 −20.2 118
								295.18		
TP	12.68	295.18	0.34	282.50						
					312.9	303.5	289.4	277.6	267.0	264.8 263.8
30+0					+40.3 82	+25.9 52	+11.8 27	5.2 −5.4 23	−10.6 44	−12.8 82 −13.8 85
		282.84						282.84	−16.74 −10.2 117	

Backsight 1+10.15

						Lt.		Rt.	
						348.4			
33+10						+39.1 110	+33.1 68	+32.4 29	30.3 3.6
+78.12	P.O.T.		2.47	310.39	OTHUB				
+60						346.8 +37.1 102	336.2 +26.5 80	323.8 +14.1 61	309.7 5.2
33+25						341.3 +31.1 90	353.2 +26.0 55	320.7 +12.0 26	307.2 5.7
TP	6.20	31286	0.80	306.66					312.86
+82						334.6 +29.9 93	328.1 +23.4 68	316.8 +13.1 35	304.7 2.8
31+50						325.6 +28.8 92	313.3 +16.5 53	306.0 +9.2 26	296.8 10.7
		307.46							307.46

						Lt.		Rt.	
						301.3			
						-8.0 41	-18.7 48	-28.9 89	-36.8 110
						300.3	290.4	280.4	272.5
						-9.4 24	-16.8 45	-25.4 79	-30.3 97
						299.6	290.8	284.4	278.9
						-7.6 22	-16.4 42	-22.8 77	-28.3 95
						294.5	285.5		276.9
						-10.2 26	-19.2 61		-27.8 87
						289.4	279.1		271.3
						-7.4 24	-17.7 61		-25.5 101

	Lt.				Rt.		
	360.4	340.6	327.9	312.3	301.9	292.4	282.9	267.4
3+35	+48 1 / 103	+28 3 / 57	+15 6 / 28	0.6	-10 4 / 18	-19 9 / 33	-29 4 / 47	-14 9 / 76
	364.5	343.6	326.1	310.3	292.4	275.3	265.4	
3+40	+54 2 / 118	+33 3 / 68	+15 8 / 29	2.6	-12 9 / 19	-35 0 / 56	-44 9 / 79	
	349.2	338.9	319.9	307.6	298.4	281.4	268.9	263.1
3+50	+41 6 / 95	+31 3 / 69	+12 6 / 27	5.3	-9 2 / 19	-20 5 / 39	-32 9 / 71	-44 5 / 91
	343.7	339.7	319.8	306.5	295.2	277.9	265.5	
3+70	+37 2 / 91	+33 3 / 78	+12 2 / 53	6.4	-11 3 / 22	-28 6 / 81	-41 0 / 101	
	344.3	328.2	313.9	298.1	290.0	279.3	263.0	
3+85	+46 2 / 100	+30 1 / 61	+15 8 / 33	14.8	-8 1 / 23	+1 8 / 60	-35 1 / 120	

8/12/86

8/12/86

						Lt		Rt	
TP	0.16	289.15	12.53	288.99					
						321.0	306.7	285.7	274.7	252.4
+50						+25.2 100	+21.2 72	+10.9 29	5.7	-10.1 23	-21.1 48	-43.4 94
					37+29.90 07Z Hub			301.52				
TP	0.45	301.52	12.14	301.07		338.0	329.8	319.2	305.8	294.6	283.3	255.3
37+0						+32.2 100	+23.4 61	+13.4 33	7.4	-11.2 22	-22.5 43	-50.5 104
						351.5	335.8	325.0	309.1	296.0	284.2	267.1
+50						+41.8 110	+26.1 61	+15.3 33	3.5	-13.7 26	-25.5 45	-43.6 88
+29.35	P.O.T.		1.65		07Z Hub							
						353.3	339.3	328.6	312.7	297.6	278.9	265.9
36+0						+40.6 98	+26.6 58	+16.9 25	0.5	-15.1 26	-33.8 59	-46.8 85
								313.21				
TP	1.83	313.21	1.48	311.38		357.6	340.9	325.6	310.4	299.0	281.0	260.6
35+60						+47.2 98	+30.5 57	+15.3 28	2.5	-11.4 21	-29.4 47	-49.8 100
		312.86						312.86				

						Lt.		Cl		Rt.	
+36.96	P.O.T		2.86		O.T.B. Hub	300.26	280.1	267.8	260.7	255.8	248.1	237.0
39+0						+39.6 131	+19.4 74	+7.1 32	3.6	-4.9 25	-12.6 72	-21.7 114
+90						295.0 +32.8 124	280.7 +23.5 84	268.7 +11.5 45	262.6 +5.4 20	257.2 7.1	251.4 -5.6 35	248.3 -8.9 61	239.3 -17.9 119
+75						288.9 +27.4 120	275.6 +14.1 79	264.4 +2.9 43	264.8 +3.3 25	261.5 2.8	256.5 -5.0 13	252.4 -9.1 40	246.7 -14.8 71	241.3 -20.2 107
TP	0.42	264.26	12.90	263.84					264.26					
+50						280.1 +14.5 114	275.7 +10.1 92	273.2 +7.6 56	271.1 +5.5 31	265.6 1.1	259.6 -6.0 27	250.8 -14.8 69	245.0 -20.6 100	
TP	0.46	276.74	12.87	276.28					276.74					
38+0						294.0 +12.5 100	294.5 +13.0 85	296.1 +14.6 62	282.0 +10.5 33	281.6 7.6	273.8 -7.7 24	262.5 -19.0 51	244.0 -37.5 102	
		289.15							289.15					

L. Line

TP	2.47	231.71	998	229.24	2" Pipe at Lot 1 20/40+98
41+0					
+50					
TP	0.27	229.22	1285	228.95	
40+15					
+90					
TP	0.16	251.80	1262	251.64	
39+50					
		264.26			

	Lt.		Rt.	
262.6	237.4	231.7	224.7	216.3
+34.6	+9.4	+3.7	-3.3	-1.7
141	86	33	55	100
267.7	253.6	241.6	229.5	229.2
+34.2	+20.1	+8.1	-4.0	-4.0
109	76	41	68	108
287.6	265.7	250.4	233.9	232.3
+48.9	+25.0	+9.7	-6.8	-8.4
114	83	32	60	106
292.7	279.0	265.1	236.9	234.8
+44.2	+30.5	+16.6	-11.6	-13.7
99	63	32	56	110
304.46	286.0	274.6	245.5	237.2
+45.2	+26.7	+15.2	-13.8	-22.1
100	57	26	43	117

228.0	225.8			
11.2	-2.2			
	23			
233.5	230.8			
5.7	-2.7			
	30			
239.22				
240.1	235.0			
11.1	-5.1			
	27			
248.5	239.8			
5.3	-8.7			
	26			
251.80				
19.3	15.1.8			
5.0	-7.5			
	20			
264.26				

						Lt.				Rt.		
										& Level		
43+0						224.8	222.0	221.9	218.9	221.4	222.3	223.9	225.4	239.9	231.5
						+2.5	-0.3	-0.4	-3.4	-0.9	9.4	+1.6	+3.1	+17.6	+29.2
						113	94	61	40	20		27	45	76	103
								2 Walls							
7+50	P.O.T				229.9	227.1	220.1	221.3	220.7	222.3	222.29	224.3	224.9	222.0	235.1
					+7.6	-0.6	-1.1	-1.0	-1.6	0.0	.9	+2.0	+2.6	+4.7	+13.4
					109	45	42	25	15	11		25	54	92	108
											07 Hub				
42+0						230.9	226.3	222.2	221.8	223.8		225.3	225.7	224.4	
						+7.1	+2.5	-1.1	-2.0	7.9		+1.5	+1.9	+3.6	
						112	61	30				23	72	100	
									5 Walls						
					234.7										
+50					+9.9	230.2	226.8	224.0	224.5	224.8		224.9	226.3	227.6	
					113	+5.4	+2.0	-0.8	-0.3	1.9		+0.1	+1.5	+2.3	
						77	35	33	5			31	60	100	
									Open Stairs						
+30						241.4	231.2	227.3	223.0	223.8	7.9	225.8	226.2	228.3	
						+17.6	+7.1	+3.5	-0.8			+2.0	+2.4	+4.5	
						118	49	16				32	63	110	
									1 Wall						
									5 Sides						
+18	" "		7.8	23.9	5 Walls										
41+16	For Profile		4.9	26.8											
		231.71								223.1					

						Lt.		Ct.		Rt.	
TP	12.44	220.86	0.20	208.42				265.5	277.0	287.8	301.6
45+0						Sec'd for Lt = 1737.18		24	+11.5 25	+22.3 60	+36.1 102
+73.88	BC. Rt.					220.2 -10.4 103	235.5 -25.1 65	247.6 -12.0 29	270.5 7.99 07446	270.7 +10.1 26	284.9 +24.3 73	298.1 +33.5 100
TP	12.87	268.62	0.08	255.75				268.62			
+50						217.2 -38.5 100	235.5 -20.2 51	246.1 -9.6 24	255.7 0.1	276.4 +10.7 36	275.4 +19.7 63	290.2 +34.5 102
44+0						220.8 -23.6 111	217.8 -26.4 69	227.0 -17.2 33	244.2 11.6	255.8 +11.6 28	266.1 +21.9 60	280.9 +36.7 103
TP	12.86	255.83	0.10	243.47				255.83			
TP	12.42	243.67	0.46	231.25							
43+50						219.7 -4.9 110	220.5 -4.1 74	222.6 -2.0 29	231.6 7.1	236.1 +11.5 24	250.9 +26.3 57	268.7 +44.1 103
		231.71						231.71			

						Lt.		Rt.	
						279.0	294.6	311.7	324.0
						-15.6	1.5	+17.1	+29.4
						38	130	62	110
45+25									
TP	2.91	296.13	0.23	293.22			296.13		
						282.1	292.5	309.0	324.4
46+0						-10.3	1.0	+16.6	+32.0
						25	22	52	97
						282.0	290.4	311.3	327.2
45+80						-8.3	3.1	+21.0	+37.3
						19 Approx	+9.8	71	106
						22	128		
						281.9	291.5	299.7	314.0
45+50						11.6	+9.7	+17.9	+32.2
							25	48	99
TP	12.78	293.45	0.19	280.67			293.45		
						275.0	284.2	295.0	308.1
45+25						6.9	+9.2	+20.0	+33.1
							27	58	102
BM	45+75 Lt		1.70	279.16	∅ Post Hub 477+19.61 279.15 Page 13		280.86		
		280.86							

∅ Hub 6' Lt

						Lt.		Rt.	
TP	6.52	242.26	11.39	235.74	07 POC 4870	230.4	226.4	225.0	227.6	235.7	243.3	255.1	272.3
4870						-5.3 117	-9.2 84	-10.7 41 - Bottom Ditch	-8.1 30	11.4	+7.6 25	+20.0 59	+36.6 104
TP	0.41	247.13	12.63	246.72						247.13			
+50						221.6 -10.7 104 - Ditch	227.4 -21.9 70	238.0 -14.3 48	245.7 -1.6 23	252.4 7.0	258.8 +6.5 25	267.9 +15.6 53	286.0 +33.7 104
TP	0.39	259.35	12.60	258.96						259.35			
TP	0.54	271.56	12.90	271.02									
4710						233.1 -43.0 108	255.5 -20.6 62	267.4 -8.7 31	276.1 7.8		288.2 +4.6 26	289.0 +12.9 76	300.5 +24.4 110
TP	0.59	283.92	12.80	283.33						283.92			
+70	POC						261.2 -27.0 72	275.9 -12.3 32	286.16 7.97 07 Hub		294.0 +5.8 27	298.6 +10.4 78	308.4 +20.2 104
4610							270.6 -22.3 56	282.0 +10.9 27	292.9 32		301.6 +8.7 30	305.6 +12.7 74	318.9 +26.0 116
		296.13								296.13			

50+70					
TP	12.64	267.07	0.04	254.43	
TP	12.30	254.47	0.09	242.17	
+50					
49+70	P.O.C.				
+50					
48+25					
		242.26			

	Lt.		Rt.	
	279.1	260.3	256.8	251.0	244.0	236.1
	+32.9	+3.5	10.3	-5.8	-12.8	-20.7
	50=Top Fill	12=Toe Slope Fill		22	65	110=Bottom Ditch
		267.07				
	275.8	253.4	248.9	242.2	237.5	235.2	234.9	240.2
	+33.6	+11.2	+7.7	0.1	-4.7	-7.0	-7.3	-2.0
	87=Top Fill	43=Toe Fill	28		28	52	79=Ditch	125
261.1	252.1	240.7	232.0	231.34	232.1	233.7	240.9	
+29.6	+20.6	+9.2	+0.5	10.72	+1.2	+2.2	+9.4	
104	72	43	17	Ditch	33	72	111	
241.5	233.2	228.4	227.7	229.7	231.7	237.9	246.4	259.2
+11.8	+3.5	-1.3	-2.0	12.6	+2.0	+8.2	+16.7	+29.5
116	78	47	12=Bottom Ditch		32	44	70	163
235.1	229.4	227.7	226.4	231.9	238.4	251.3	265.8	
+3.2	-2.5	-4.2	-5.5	10.4	+6.5	+19.4	+33.4	
113	70	40	23=Bottom Ditch		24	63	106	
		242.26						

"L" Line

+50					
+27	= Culvert on Rt				
51+0					
+80					
TP	12.99	291.19	0.48	278.20	
+50					
TP	11.89	278.68	0.28	266.79	
50+25					
		267.07			

Lt. / Rt.

	Lt.				Rt.			
		283.34	283.9	284.9	293.4	254.6	252.8	
		7.85 on Pay	+0.6	+1.6 -29.9 89		-28.7 87	-30.5 101	
		287.8		51.8		48.3		
		8.7		-3.5 68		-5.5 18		
		281.5	282.8	278.3	244.8	242.8		
		9.7 = Slope Rt	+1.3 8	-9.2 28	-20.5 63	-26.7 77		
					-36.1 89	-38.9 102		
	280.6	281.7	270.6	254.8	244.8	242.8		
+80	-1.1 12 Slope	9.5 = Top Fill	-11.1 11	-26.9 42	-36.9 77	-39.3 98		
		291.19						
	279.4	280.9	271.9	259.3	248.0	238.1		
+50	+7.5 21 = Slope Rt	+9.0 14 = Top Fill	6.8	-12.6 23 = Toe Fill Slope	-23.9 64	-40.8 96		
		278.68						
	272.5	279.6	262.7	255.3	245.2	237.2		
50+25	+15.8 36 = Slope Rt	+16.9 29 = Top Fill	4.1 = Top Fill Slope	-7.4 26	-17.5 68	-25.5 120 = Bottom Ditch		
		267.07						

							Lt.	Rt.
							292.03	
+42	B.C. Rt.						3.29	291.9 / 293.1 / 277.9 / 273.5
								-1.0 / +0.2 / -15.0 / -19.4
								32 / 29 / 49 / 98
								on RR Spike
								52+87.57
								21 = 5% Rt.
53+0							290.82	
							3.10	290.2 / 291.2 / 274.6 / 272.9
								-0.6 / +0.4 / -16.5 / -17.9
								21 / 28 / 52 / 82
								5% Rt.
							288.14	
+50							8.08	288.1 / 289.8 / 270.5 / 266.9
								0.0 / +1.7 / -17.6 / -21.5
								21 / 30 / 60 / 95
								5% Rt.
							296.28	
BM	8.69	296.28 N	2.66	287.53		on RR Spike 52+87.57 ℄ Montezuma Rd.	2	
							286.90	
+26.40	E.C.						4.29	287.2 / 288.6 / 269.1 / 269.6
								+0.3 / +1.7 / -17.8 / -21.3
								21 / 29 / 53 / 94
								5% Rt.
							285.53	
52+0							6.66	287.0 / 263.5 / 242.7
								+1.5 / -22.0 / -22.8
								28 / 59 / 86
								5% Rt.
		291.19					291.19	

Lt. Z Rt. 79

DIETZGEN'S RAILROAD CURVE AND REDUCTION TABLES

Copyright, 1914, by Eugene Dietzgen Co., New York City



CURVE FORMULAS

Radius=R=$\frac{50}{\sin. D/2}$ (1) Degree of Curve=D and sin. $\frac{D}{2}=\frac{50}{R}$ (2)

Tangent=T=R tan $\frac{\Delta}{2}$ (3) Length of Curve=L=$100\frac{\Delta}{D}$ (4)

Middle ordinate=M=R(1—cos. $\frac{\Delta}{2}$) (5)=R vers $\frac{\Delta}{2}$ (6)

External=E=T tan $\frac{\Delta}{4}$ (7)=R ÷ cos. $\frac{\Delta}{2}$—R (8)=R exsec $\frac{\Delta}{2}$ (9)

Long Chord=C=2 R sin. $\frac{\Delta}{2}$ (10) △=Central Angle

EXPLANATION AND USE OF TABLES

Stations.—Given P. I.=Sta. 161+60.35 to find Sta. of P. C. and P. T. △=62° 10′ D=8° 20′. From Table IV for 1° curve T=3454.1 and ÷8⅓=414.49 ft. From Table V correction=.36 or T=414.85 ft. P. C.=Sta. P.I.—T=157 +45.50. Also from (4) L=746.00 and P. T.=Sta. P. C.+L=164+91.50.

Offsets.—Tangent offsets vary (approximately) directly with D and with square of the distance. Thus tangent offset for Sta. 158 on above curve is 2.16 ft. found as follows. From Table III tangent offset for 100 ft.=7.27 ft. Distance=158—Sta. P. C.=54.50, hence offset=7.27 $(54.50 \div 100)^2$=2.16 ft. Also square of any distance divided by twice the radius equals (approximately) the distance from tangent to curve. Thus $(54.50)^2 \div (2 \times 688.26)$=2.16 ft.

Deflections.—Deflection angle=½ D for 100 ft., ¼ D for 50 ft., etc. For c ft.=(in minutes) .3 x C x D° or=defl. for 1 ft. from Table III x C. For Sta. 158 of above curve=.3 x 54.5 x 8⅓=136.2′ or 2° 16.2′, or=2.50 x 54.5=136.2′ from Table III. For Sta. 159 deflection angle=2° 16.2′ +8° 20′ ÷2=6° 26.2′, etc.

Externals.—May be found in similar manner to tangents. Thus E for curve above is 115.37. For from Table IV for 1° curve E=960.6 for 8° 20′=960.6 ÷8⅓=115.27 and from Table V correction=.10 or E=115.37 ft. Or suppose △=32° and E is measured and found to be 42 ft. What is D? From Table IV E=230.9 and ÷42=5.5 or D=5° 30′.

ternal

7.57
0.16
0.75
2.35
3.97
5.60

7.24
8.90
0.57
2.25
3.95
5.66

7.38
9.12
0.87
2.63
.41
5.20

.00
.82
.65
.50
.35
.23

.11
.01
.93
.85
.79
.75

.71
.69
.69
.70
.72
.76

.81
.86
.95
.04
.15
.27

.41
.55
.72
.89
08
29

51
74
99
25
53
82

12
44
77
12
48
86

Table I.—Minutes in Decimals of a Degree.

1′	.0167	11′	.1833	21	.3500	31′	.5167	41′	.6833	51′	.8500
2	.0333	12	.2000	22	.3667	32	.5333	42	.7000	52	.8667
3	.0500	13	.2167	23	.3833	33	.5500	43	.7167	53	.8833
4	.0667	14	.2333	24	.4000	34	.5667	44	.7333	54	.9000
5	.0833	15	.2500	25	.4167	35	.5833	45	.7500	55	.9167
6	.1000	16	.2667	26	.4333	36	.6000	46	.7667	56	.9333
7	.1167	17	.2833	27	.4500	37	.6167	47	.7833	57	.9500
8	.1333	18	.3000	28	.4667	38	.6333	48	.8000	58	.9667
9	.1500	19	.3167	29	.4833	39	.6500	49	.8167	59	.9833
10	.1667	20	.3333	30	.5000	40	.6667	50	.8333	60	1.0000

Table II.—Inches in Decimals of a Foot.

1–16	3–32	⅛	3–16	¼	5–16	⅜	½	⅝	¾	⅞
.0052	.0078	.0104	.0156	.0208	.0260	.0313	.0417	.0521	.0625	.0729

1	2	3	4	5	6	7	8	9	10	11
.0833	.1667	.2500	.3333	.4167	.5000	.5833	.6667	.7500	.8333	.9167

Table III.—Radii, Ordinates and Deflections.

Deg.	Radius	Mid. Ord.	Tan. Offset	Def. for 1 Foot	Deg.	Radius	Mid. Ord.	Tan Offset	Def. for 1 Foot
0° 10′	34377.5	.036	.145	0.05′	7°	819.02	1.528	6.105	2.10′
20	17188.8	.073	.291	0.10	20′	781.84	1.600	6.395	2.20
30	11459.2	.109	.436	0.15	30	764.49	1.637	6.540	2.25
40	8594.42	.145	.582	0.20	40	747.89	1.673	6.685	2.30
50	6875.55	.182	.727	0.25	8	716.78	1.746	6.976	2.40
1	5729.65	.218	.873	0.30	20	688.16	1.819	7.266	2.50
10	4911.15	.255	1.018	0.35	30	674.69	1.855	7.411	2.55
20	4297.28	.291	1.164	0.40	40	661.74	1.892	7.556	2.60
30	3819.83	.327	1.309	0.45	9	637.28	1.965	7.846	2.70
40	3437.87	.364	1.454	0.50	20	614.56	2.037	8.136	2.80
50	3125.36	.400	1.600	0.55	30	603.80	2.074	8.281	2.85
2	2864.93	.436	1.745	0.60	40	593.42	2.110	8.426	2.90
10	2644.58	.473	1.891	0.65	10	573.69	2.183	8.716	3.00
20	2455.70	.509	2.036	0.70	30	546.44	2.292	9.150	3.15
30	2292.01	.545	2.181	0.75	11	521.67	2.402	9.585	3.30
40	2148.79	.582	2.327	0.80	30	499.06	2.511	10.02	3.45
50	2022.41	.618	2.472	0.85	12	478.34	2.620	10.45	3.60
3	1910.08	.655	2.618	0.90	30	459.28	2.730	10.89	3.75
10	1809.57	.691	2.763	0.95	13	441.68	2.839	11.32	3.90
20	1719.12	.727	2.908	1.00	30	425.40	2.949	11.75	4.05
30	1637.28	.764	3.054	1.05	14	410.28	3.058	12.18	4.20
40	1562.88	.800	3.199	1.10	30	396.20	3.168	12.62	4.35
50	1494.95	.836	3.345	1.15	15	383.07	3.277	13.05	4.50
4	1432.69	.873	3.490	1.20	30	370.78	3.387	13.49	4.65
10	1375.40	.909	3.635	1.25	16	359.27	3.496	13.92	4.80
20	1322.53	.945	3.718	1.30	30	348.45	3.606	14.35	4.95
30	1273.57	.982	3.926	1.35	17	338.27	3.716	14.78	5.10
40	1228.11	1.018	4.071	1.40	18	319.62	3.935	15.64	5.40
50	1185.78	1.055	4.217	1.45	19	302.94	4.155	16.51	5.70
5	1146.28	1.091	4.362	1.50	20	287.94	4.374	17.37	6.00
10	1109.33	1.127	4.507	1.55	21	274.37	4.594	18.22	6.30
20	1074.68	1.164	4.653	1.60	22	262.04	4.814	19.08	6.60
30	1042.14	1.200	4.798	1.65	23	250.79	5.035	19.94	6.90
40	1011.51	1.237	4.943	1.70	24	240.49	5.255	20.79	7.20
50	982.64	1.273	5.088	1.75	25	231.01	5.476	21.64	7.50
6	955.37	1.309	5.234	1.80	26	222.27	5.697	22.50	7.80
10	929.57	1.346	5.379	1.85	27	214.18	5.918	23.35	8.10
20	905.13	1.382	5.524	1.90	28	206.68	6.139	24.19	8.40
30	881.95	1.418	5.669	1.95	29	199.70	6.360	25.04	8.70
40	859.92	1.455	5.814	2.00	30	193.18	6.583	25.88	9.00

Note. Chord Deflection=2 times tangent deflection.

Table IV.—Tangents and Externals to a 1° Curve.

Central Angle	Tangent	External	Central Angle	Tangent	External	Central Angle	Tangent	External
1°	50.00	.22	11°	551.70	26.50	21°	1061.9	97.57
10′	58.34	.30	10′	560.11	27.31	10′	1070.6	99.16
20	66.67	.39	20	568.53	28.14	20	1079.2	100.75
30	75.01	.49	30	576.95	28.97	30	1087.8	102.35
40	83.34	.61	40	585.36	29.82	40	1096.4	103.97
50	91.68	.73	50	593.79	30.68	50	1105.1	105.60
2	100.01	.87	12	602.21	31.56	22	1113.7	107.24
10	108.35	1.02	10	610.64	32.45	10	1122.4	108.90
20	116.68	1.19	20	619.07	33.35	20	1131.0	110.57
30	125.02	1.36	30	627.50	34.26	30	1139.7	112.25
40	133.36	1.55	40	635.93	35.18	40	1148.4	113.95
50	141.70	1.75	50	644.37	36.12	50	1157.0	115.66
3	150.04	1.96	13	652.81	37.07	23	1165.7	117.38
10	158.38	2.19	10	661.25	38.03	10	1174.4	119.12
20	166.72	2.43	20	669.70	39.01	20	1183.1	120.87
30	175.06	2.67	30	678.15	39.99	30	1191.8	122.63
40	183.40	2.93	40	686.60	40.99	40	1200.5	124.41
50	191.74	3.21	50	695.06	42.00	50	1209.2	126.20
4	200.08	3.49	14	703.51	43.03	24	1217.9	128.00
10	208.43	3.79	10	711.97	44.07	10	1226.6	129.82
20	216.77	4.10	20	720.44	45.12	20	1235.3	131.65
30	225.12	4.42	30	728.90	46.18	30	1244.0	133.50
40	233.47	4.76	40	737.37	47.25	40	1252.8	135.35
50	241.81	5.10	50	745.85	48.34	50	1261.5	137.23
5	250.16	5.46	15	754.32	49.44	25	1270.2	139.11
10	258.51	5.83	10	762.80	50.55	10	1279.0	141.01
20	266.86	6.21	20	771.29	51.68	20	1287.7	142.93
30	275.21	6.61	30	779.77	52.89	30	1296.5	144.85
40	283.57	7.01	40	788.26	53.97	40	1305.3	146.79
50	291.92	7.43	50	796.75	55.13	50	1314.0	148.75
6	300.28	7.86	16	805.25	56.31	26	1322.8	150.71
10	308.64	8.31	10	813.75	57.50	10	1331.6	152.69
20	316.99	8.76	20	822.25	58.70	20	1340.4	154.69
30	325.35	9.23	30	830.76	59.91	30	1349.2	156.70
40	333.71	9.71	40	839.27	61.14	40	1358.0	158.72
50	342.08	10.20	50	847.78	62.38	50	1366.8	160.76
7	350.44	10.71	17	856.30	63.63	27	1375.6	162.81
10	358.81	11.22	10	864.82	64.90	10	1384.4	164.86
20	367.17	11.75	20	873.35	66.18	20	1393.2	166.95
30	375.54	12.29	30	881.88	67.47	30	1402.0	169.04
40	383.91	12.85	40	890.41	68.77	40	1410.9	171.15
50	392.28	13.41	50	898.95	70.09	50	1419.7	173.27
8	400.66	13.99	18	907.49	71.42	28	1428.6	175.41
10	409.03	14.58	10	916.03	72.76	10	1437.4	177.55
20	417.41	15.18	20	924.58	74.12	20	1446.3	179.72
30	425.79	15.80	30	933.13	75.49	30	1455.1	181.89
40	434.17	16.43	40	941.69	76.86	40	1464.0	184.08
50	442.55	17.07	50	950.25	78.26	50	1472.9	186.29
9	450.93	17.72	19	958.81	79.67	29	1481.8	188.51
10	459.32	18.38	10	967.38	81.09	10	1490.7	190.74
20	467.71	19.06	20	975.96	82.53	20	1499.6	192.99
30	476.10	19.75	30	984.53	83.97	30	1508.5	195.25
40	484.49	20.45	40	993.12	85.43	40	1517.4	197.53
50	492.88	21.16	50	1001.7	86.90	50	1526.3	199.82
10	501.28	21.89	20	1010.3	88.39	30	1535.3	202.12
10	509.68	22.62	10	1018.9	89.89	10	1544.2	204.44
20	518.08	23.38	20	1027.5	91.40	20	1553.1	206.77
30	526.48	24.14	30	1036.1	92.92	30	1562.1	209.12
40	534.89	24.91	40	1044.7	94.46	40	1571.0	211.48
50	543.29	25.70	50	1053.3	96.01	50	1580.0	213.86

DIAGRAM
HORIZONTA
DIS
FROM STA

Enter on the horiz
of the stadia readi
stadia constant (us
run vertically upw
line representing t
location of this p
the dotted line
gives the correct
from the entering
"f + c" (usually
be added to obta
Distance The re
scale plus about
5° of vertical angl
is the Vertical D

© 1914 BY J.K.F



55 + 51.41
51 + 45.50
4 05 91

DISTANCES FROM CENTER OF ROADWAY FOR CROSS-SECTIONING.

Roadway 16 feet wide. Side Slopes 1 on 1½

For Single Track Embankment.

H	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	H
0	8.0	8.2	8.3	8.5	8.6	8.8	8.9	9.1	9.2	9.4	0
1	9.5	9.7	9.8	10.0	10.1	10.3	10.4	10.6	10.7	10.9	1
2	11.0	11.2	11.3	11.5	11.6	11.8	11.9	12.1	12.2	12.4	2
3	12.5	12.7	12.8	13.0	13.1	13.3	13.4	13.6	13.7	13.9	3
4	14.0	14.2	14.3	14.5	14.6	14.8	14.9	15.1	15.2	15.4	4
5	15.5	15.7	15.8	16.0	16.1	16.3	16.4	16.6	16.7	16.9	5
6	17.0	17.2	17.3	17.5	17.6	17.8	17.9	18.1	18.2	18.4	6
7	18.5	18.7	18.8	19.0	19.1	19.3	19.4	19.6	19.7	19.9	7
8	20.0	20.2	20.3	20.5	20.6	20.8	20.9	21.1	21.2	21.4	8
9	21.5	21.7	21.8	22.0	22.1	22.3	22.4	22.6	22.7	22.9	9
10	23.0	23.2	23.3	23.5	23.6	23.8	23.9	24.1	24.2	24.4	10
11	24.5	24.7	24.8	25.0	25.1	25.3	25.4	25.6	25.7	25.9	11
12	26.0	26.2	26.3	26.5	26.6	26.8	26.9	27.1	27.2	27.4	12
13	27.5	27.7	27.8	28.0	28.1	28.3	28.4	28.6	28.7	28.9	13
14	29.0	29.2	29.3	29.5	29.6	29.8	29.9	30.1	30.2	30.4	14
15	30.5	30.7	30.8	31.0	31.1	31.3	31.4	31.6	31.7	31.9	15
16	32.0	32.2	32.3	32.5	32.6	32.8	32.9	33.1	33.2	33.4	16
17	33.5	33.7	33.8	34.0	34.1	34.3	34.4	34.6	34.7	34.9	17
18	35.0	35.2	35.3	35.5	35.6	35.8	35.9	36.1	36.2	36.4	18
19	36.5	36.7	36.8	37.0	37.1	37.3	37.4	37.6	37.7	37.9	19
20	38.0	38.2	38.3	38.5	38.6	38.8	38.9	39.1	39.2	39.4	20
21	39.5	39.7	39.8	40.0	40.1	40.3	40.4	40.6	40.7	40.9	21
22	41.0	41.2	41.3	41.5	41.6	41.8	41.9	42.1	42.2	42.4	22
23	42.5	42.7	42.8	43.0	43.1	43.3	43.4	43.6	43.7	43.9	23
24	44.0	44.2	44.3	44.5	44.6	44.8	44.9	45.1	45.2	45.4	24
25	45.5	45.7	45.8	46.0	46.1	46.3	46.4	46.6	46.7	46.9	25
26	47.0	47.2	47.3	47.5	47.6	47.8	47.9	48.1	48.2	48.4	26
27	48.5	48.7	48.8	49.0	49.1	49.3	49.4	49.6	49.7	49.9	27
28	50.0	50.2	50.3	50.5	50.6	50.8	50.9	51.1	51.2	51.4	28
29	51.5	51.7	51.8	52.0	52.1	52.3	52.4	52.6	52.7	52.9	29
30	53.0	53.2	53.3	53.5	53.6	53.8	53.9	54.1	54.2	54.4	30
31	54.5	54.7	54.8	55.0	55.1	55.3	55.4	55.6	55.7	55.9	31
32	56.0	56.2	56.3	56.5	56.6	56.8	56.9	57.1	57.2	57.4	32
33	57.5	57.7	57.8	58.0	58.1	58.3	58.4	58.6	58.7	58.9	33
34	59.0	59.2	59.3	59.5	59.6	59.8	59.9	60.1	60.2	60.4	34
35	60.5	60.7	60.8	61.0	61.1	61.3	61.4	61.6	61.7	61.9	35
36	62.0	62.2	62.3	62.5	62.6	62.8	62.9	63.1	63.2	63.4	36
37	63.5	63.7	63.8	64.0	64.1	64.3	64.4	64.6	64.7	64.9	37
38	65.0	65.2	65.3	65.5	65.6	65.8	65.9	66.1	66.2	66.4	38
39	66.5	66.7	66.8	67.0	67.1	67.3	67.4	67.6	67.7	67.9	39
40	68.0	68.2	68.3	68.5	68.6	68.8	68.9	69.1	69.2	69.4	40

Example—If point is 22.6 ft. above grade, how far should it be from center line to be a slope stake point? Ans. from Table 41.9. For same slopes but other widths of roadbed correct above figures by one-half difference in width of roadbed; thus in example above for 20 ft. roadbed distance will be 41.9+(20—16)÷2 or 2 ft. added to 41.9 =43 9. For slopes of 1 on 1 see inside of front cover.

MADE IN U.S.A.